

Power Supply

ME-16000

Features

- 1- Very compact metal cased power supply
- 2- Universal input AC input,full range
- 3- Natural air cool
- 4- Screw terminal block
- 5- 1 year product warranty
- 6- Protection: short-circuit, overload,overcurrent



Specifications		
Output	DC Voltage (V)	12V
	Voltage Range	11.40-12.60V
	Rated Current (A)	5A
	Current Range (A)	0 - 5A
	Rated Power (W)	60W
	Ripple & Noise (Mvp-p)	120mVP-P
	voltage accuracy	±1%
	Line Regulation	±1%
	Load Regulation	±1%
Input	Voltage Range (V)	AC100- 265V
	Frequency Range (Hz)	50~60Hz
	AC Current (A)	1.1~0.55A/110/220VAC
	Efficiency (Typ)	85%
Protection	Overload Protection	110 ~ 150% rated output power Protection type: hiccup,automatic restoration after abnormality remove
	short circuit protection	Protection type: restart to open the power supply and automatic restoration after output short circuit is removed
Environment	Working Temp	-10~+40°C
	Working Humidity	20 ~ 90% RH, non-condensing
	Storage Temp& Humidity	-20°C ~ 85°C;10~95%RH
	Vibration resistance	10~500Hz,2G per 1min,X、 Y、 Z axis for each 60 minutes
Others	Dimensions	110*78*36mm (L*W*H)
	Weight	0.23kg